

## Title

### **Spectacles Set with Detachable Magnetic Shelter Frame**

## Cross-Reference of Related Application

5

This is a Continuation-In-Part application of a non-provisional application having an application number 10/278,497 and a filing date of October 24, 2004.

## Background of the Present Invention

### **Field of Invention**

10

The present invention relates to a spectacle frame, and more particularly to a spectacles set, which comprises a detachable magnetic shelter frame adapted for detachably mounting in front of a primary spectacle frame by means of magnetic attraction.

### **Description of Related Arts**

15

Shelter frames are widely used today. A conventional shelter frame, such as clip-on sunglasses, comprises a plurality of clipping claws for detachably mounted on a shortsighted or farsighted sunglasses so that the wearer does not need to carry and pay for another pair of shortsighted or farsighted sunglasses. However, the metal made clipping claws may scratch the lenses of the primary eyeglasses during the attaching operation.

20

Also, the wearer requires both hands to align and engage the conventional clip-on sunglasses on the primary eyeglasses in correct position. It is troublesome and dangerous for a wearer to use his or her both hands to wear such clip-on sunglasses on the regular glasses while he or she is driving.

25

In order to solve the problem of the above mentioned clip-on sunglasses, magnetic attachment is recently introduced into the eyeglasses industry, such as U.S. patents 5416537, 5568207, 5642177, 5737054, and 5975691. For example, in U.S. patent 5568207, a primary pair of magnet members is affixed on two side extensions of a primary spectacle frame respectively. A shelter frame, such as sunglasses, includes a pair

of arms for resting over the upper side extensions for preventing the shelter frame from moving downward relative to the primary spectacle for engaging with the primary magnet members of the primary spectacle frame so as to stably attach the shelter frame to the primary spectacle frame. However, the users have to align two pairs of magnet  
5 members. If the auxiliary magnet members of the sunglasses are misaligned with the primary magnet members of the primary spectacle frame, the sunglass will fall down from the primary spectacle frame easily.

Moreover, the magnet members are firmly affixed to the spectacle frame of the primary spectacle. Once the spectacle frame is accidentally bent its shape, the shelter  
10 frame may not precisely mounted on the primary spectacle by means of the magnet attachment. Furthermore, the spectacle frame of the primary spectacle must be altered to fit the magnet members thereto such that the magnet members will destroy the aesthetic appearance of the primary spectacle.

### Summary of the Present Invention

15 A main object of the present invention is to provide a spectacles set which comprises a detachable shelter frame adapted for detachably mounting in front of a primary spectacle frame by means of magnetic attachment arrangement, so as to precisely interlock the detachable shelter frame with the primary spectacle frame.

Another object of the present invention is to provide a spectacles set wherein  
20 each of the nose supports of the primary spectacle frame is made of a kind of metal having magnetic attraction ability such that the primary spectacle frame does not require to change the original structural design to incorporate with the detachable shelter frame.

Another object of the present invention is to provide a spectacles set, wherein the detachable shelter frame adapted for precisely and easily mounting in front of the  
25 primary spectacle frame by means of magnetic attachment arrangement without the risk of scratching the lenses of the primary spectacle frame.

Another object of the present invention is to provide a spectacles set with detachable shelter frame, wherein the magnetic attachment arrangement is hidden behind

the frame body of the primary spectacle frame and located at the nose supports of the primary spectacle frame so as to keep the aesthetic appearance of the primary spectacle frame.

Another object of the present invention is to provide a spectacles set with detachable shelter frame, wherein the nose supports are adapted to be adjusted their positions with respect to the primary spectacle frame in order to fit the wearer, the wearer may self-adjust the magnetic attachment arrangement to align with the detachable shelter frame even the shape of the primary spectacle frame is slightly distorted.

Another object of the present invention is to provide a spectacles set with detachable shelter frame, wherein two supporting arms of the magnetic attachment arrangement ride on the primary bridge of the primary spectacle, so as to support the detachable shelter frame and further prevent the downward and sideward movement of the detachable shelter frame with respect to the primary spectacle frame.

Another object of the present invention is to provide a spectacles set with detachable shelter frame, wherein the two supporting arms of the magnetic attachment arrangement are further extended downwardly to mount on the primary bridge of the primary spectacle so as to further prevent any frontward or rearward movement of the detachable shelter frame with respect to the primary spectacle frame.

Another object of the present invention is to provide a spectacles set, wherein the wearer may merely use one hand to attach or detach the detachable shelter frame during exercising or driving.

Another object of the present invention is to provide a spectacles set with detachable shelter frame, wherein no magnet is needed to embed into the primary spectacle frame such that no magnetic field is generated around the primary spectacle frame to affect the wearer's health while he or she normally wears the primary spectacle frame.

Accordingly, in order to accomplish the above objects, the present invention provides a spectacles set comprising a primary spectacle frame and a detachable shelter frame adapted for mounting in front of the primary spectacle frame.

The primary spectacle frame comprises a frame body for mounting a pair of lenses in position, wherein the frame body comprises a primary bridge connected between the two lenses, two nose supports each of which has magnetic attraction ability extended from two inner sides of the lenses respectively, and two side extensions  
5 provided at two outer sides of the lenses for coupling a pair of temples respectively.

The detachable shelter frame comprises a shelter frame for supporting two auxiliary lenses and a pair of magnetic attachment arrangements connected to the shelter frame, wherein each of the magnetic attachment arrangements comprises a supporting arm extending rearwardly from an inner side of the shelter frame towards the respective  
10 nose support and a magnetic seat which is connected to the supporting arm and extended to magnetically attach the respective nose support of the primary spectacle frame so as to securely hold the shelter frame in front of the primary spectacle frame.

In a preferred embodiment of the present invention, the shelter frame includes a shelter bridge connected between the two auxiliary lenses and each of the supporting  
15 arms of the magnetic attachment arrangements has a riding portion rearwardly extended from the shelter bridge for riding on the primary bridge of the primary spectacle frame and a mounting portion downwardly extended from the riding portion to support the magnetic seat thereof to attach with respective nose support of the primary spectacle frame.

20 These and other objectives, features, and advantages of the present invention will become apparent from the following detailed description, the accompanying drawings, and the appended claims.

## Brief Description of the Drawings

Fig. 1 is a perspective view of a spectacles set comprising a primary spectacle frame incorporated with a detachable shelter frame according to a first preferred embodiment of the present invention.

- 5 Fig. 2 is a perspective view of the spectacles set according to the above first preferred embodiment of present invention, illustrating the detachable shelter frame being mounted in front of the primary spectacle frame.

Fig. 3 illustrates a first alternative mode of the spectacles set according to the above first preferred embodiment of the present invention.

- 10 Fig. 4 illustrates a second alternative mode of the spectacles set according to the above first preferred embodiment of the present invention.

Fig. 5 illustrates a third alternative mode of the spectacles set according to the above first preferred embodiment of the present invention.

- 15 Fig. 6 illustrates a fourth alternative mode of the spectacles set according to the above first preferred embodiment of the present invention.

Fig. 7 illustrates a fifth alternative mode of the spectacles set according to the above first preferred embodiment of the present invention.

Fig. 8 is a perspective view of a spectacles set according to a second preferred embodiment of the present invention.

- 20 Fig. 9 is a perspective view of the magnetic attachment arrangement of the spectacles set according to the above second preferred embodiment of the present invention.

Fig. 10 illustrates an alternative mode of the spectacles set according to the above second preferred embodiment of the present invention.

Fig. 11 is a perspective view of a spectacles set according to a third preferred embodiment of the present invention.

Fig. 12 is a sectional view of the spectacles set according to the above third preferred embodiment of the present invention, illustrating the detachable shelter frame being  
5 mounted in front of the primary spectacle frame.

Fig. 13 illustrates a first alternative mode of the spectacles set according to the above third preferred embodiment of the present invention.

Fig. 14 illustrates a second alternative mode of the spectacles set according to the above third preferred embodiment of the present invention.

## Detailed Description of the Preferred Embodiment

Referring to Fig. 1 of the drawings, a spectacles set according to a first preferred embodiment of the present invention is illustrated, wherein the spectacles set comprises a primary spectacle frame 10 and a detachable shelter frame 20 adapted for mounting in front of the primary spectacle frame 10.

The primary spectacle frame 10, such as a conventional spectacle frame, comprises a frame body 11 for mounting a pair of lenses 121, 122 in position, wherein the frame body 11 comprises a primary bridge 111 connected between the two lenses 121, 122, two nose supports 13, 14 extended from two inner sides of the lenses 121, 122 respectively, and two side extensions provided at two outer sides of the lenses 121, 122 for coupling a pair of temples respectively.

Each of the nose supports 13, 14 comprises a supporting member 131, 141 and an extension arm 132, 142 which has a distal end portion extended from the supporting member 131, 141 and a root end portion extended from the inner side of the respective lens 121, 122, wherein each of the extension arms 132, 142 is made of a kind of metal having magnetic attraction ability, such as mild steel, low carbon steel and high grade steel, which is attractive to magnetic material such as permanent magnet.

According to the preferred embodiment, the two extension arms 132, 142 of the nose supports 13, 14 are integrally and rearwardly extended from the frame body 11 wherein each of the extension arms 132, 142 is bent to form a shoulder portion 1321, 1421 between the distal end portion and the root end portion. As shown in Fig. 1, each of the extension arms 132, 142 is made in reverse U-shape wherein the shoulder portion 1321, 1421 is formed at a top side of the respective extension arm 132, 142 to magnetically attract with the detachable shelter frame 20. In other words, the primary spectacle frame 10 does not require modifying its original structure for mounting the detachable shelter frame 20 thereon.

The frame body 11 of the primary spectacle frame 10 can be constructed as the conventional spectacle frame to have a pair of lens rims as shown in Fig. 1 or the rimless

frame that the primary bridge 111 and the two side extensions 15, 16 are directly fastened to the edges of the two lenses 121, 122.

The detachable shelter frame 20 comprises a shelter frame 21 for supporting two auxiliary lenses 221, 222. The shelter frame 21 comprises a shelter bridge 211  
5 extended between the two auxiliary lenses 221, 222 and a pair of magnetic attachment arrangements 24, 25 connected to the shelter frame 21 for holding the shelter frame 21 in front of the primary spectacle frame 10 in position.

As shown in Fig. 1, each of the magnetic attachment arrangements 24, 25 comprises a supporting arm 241, 251 extending rearwardly from an inner side of the  
10 shelter frame 21 towards the respective nose support 13, 14 and a magnetic seat 242, 252 which is connected to the supporting arm 241, 251 and extended to magnetically attach the respective nose support 13, 14 of the primary spectacle frame 10 so as to securely hold the shelter frame 21 of the detachable shelter frame 20 in front of the frame body 11 of the primary spectacle frame 10.

Each of the magnetic seats 242, 252 comprises a magnetic housing 243, 253  
15 rearwardly extended from the respective supporting arm 241, 251 wherein each magnetic seat 242, 252 is made of non-magnetic material or soft-magnetic metal having magnetic attraction ability such as mild steel, low carbon steel and high grade steel and a magnet 244, 254 mounted in the magnetic housing 243, 253, which is arranged to face toward  
20 and align with the respective nose support 13, 14 of the frame body 11 when the detachable shelter frame 20 is mounted in front of the primary spectacle frame 10.

According to the preferred embodiment, the two supporting arms 241, 251 are in L-shaped and extended from two end portions of the shelter bridge 211, wherein each of the supporting arms 241, 251 comprises a riding portion 2411, 2511 rearwardly  
25 extended from the shelter bridge 211 to ride on the primary bridge 111 and a mounting portion 2412, 2512 downwardly and integrally extended from a rear end of the respective riding body 2411, so that the riding portions of the supporting arms 241, 251 are capable of substantially riding on the primary bridge 111 when the detachable shelter frame 20 is mounted in front of the primary spectacle frame 10 so as to support the detachable shelter  
30 frame 20 and further prevent any downward and sideward movement of the detachable shelter frame 20 with respect to the primary spectacle frame 10.



In other words, the two supporting arms 241, 251 function as a bridge clip to ride on top of the primary bridge 111 of the frame body 11 for engaging with the primary bridge 111 so as to securely interlock the shelter frame 21 of the detachable shelter frame 20 in front of the primary spectacle frame 10.

5 In addition, the two mounting portions 2412, 2512 of the two supporting arms 241, 251 of the magnetic attachment arrangement 24, 25 are further extended downwardly to mount on the primary bridge 111 of the primary spectacle frame 10 that may further prevent any frontward or rearward movement of the detachable shelter frame 20 with respect to the primary spectacle frame 10, so that besides the magnetic  
10 attachment between the two magnetic seats 242, 252 and the two magnetic holders 152, 162 respectively, the detachable shelter frame 20 can further be securely mounted and supported on the primary spectacle frame 10.

As shown in Fig. 2, the magnetic seats 242, 252 are connected to bottom ends of the mounting portions 2412, 2512 of the supporting arms 241, 251 respectively to  
15 magnetically attach to the shoulder portions 1321, 1421 of the extension arms 132, 142 of the nose supports 13, 14 respectively. Each of magnetic housings 243, 253, having a reverse U-shaped cross section, is downwardly and suspendedly affixed to the bottom (rear) end of the mounting portion 2412, 2512 of the respective supporting arm 241, 251.

Each magnet 244, 254 has a thickness smaller than a depth of the respective  
20 magnetic housing 243, 253 so as to define an engaging groove 245, 255, when the magnet 244, 254 is embedded in the magnetic housing 243, 253 for fittedly engaging with the respective shoulder portion 1321, 1421 of the respective nose support 13, 14. In other words, the engaging groove 245, 255 is defined between two sidewalls of the respective magnetic housing 243, 253.

25 In order to mount the detachable shelter frame 20 in front of the primary spectacle frame 10, the magnetic seats 242, 252 are respectively attached to the two nose supports 13, 14 by magnetically engaging the two shoulder portions 1321, 1421 of the extension arms 13, 14 in the two engaging grooves 245, 255 respectively. In addition, when the magnets 244, 254 are mounted in the magnetic housing 243, 253, the magnet  
30 field present around the two magnets 244, 254 not only guide the magnetic seats 242, 252 toward the align with the extension arms 132, 142 of the nose supports 13, 14 but also

ensure the magnetic seats 242, 252 firmly attached with the extension arms 132, 142 of the nose supports 13, 14, as shown in Fig. 2.

Fig. 3 illustrates a first alternative mode of the magnetic seat 242A, 252A wherein each of the magnetic seats 242A, 252A comprises a magnetic housing 243A, 253A extended from the bottom end of the respective supporting arm 241, 251 and two magnets 244A, 254A mounted in the magnetic housing 243A, 253A, which is arranged to face toward and align with the respective nose support 13, 14 of the frame body 11.

As shown in Fig. 3, each of the magnetic housing 243A, 253A, having a reverse U-shaped cross section, is downwardly and suspendedly affixed to the bottom end of the respective supporting arm 241, 251, wherein the two magnets 244A, 254A are received at two sidewalls of the respective magnetic housing 243A, 253A to define an engaging groove 245A, 255A between the two sidewalls thereof. Accordingly, the two magnets 244A, 254A are embedded at two sidewalls of the respective magnetic housing 243A, 253A wherein the magnetic seats 242A, 252A are respectively attached to the two nose supports 13, 14 by magnetically engaging the two shoulder portions 1321, 1421 of the extension arms 13, 14 in the two engaging grooves 245A, 255A respectively.

Fig. 4 illustrates a second alternative mode of the magnetic seat 242B, 252B wherein each of the magnetic seats 242B, 252B comprises a magnetic housing 243B, 253B extended from the bottom end of the respective supporting arm 241, 251 and a magnet 244B, 254B mounted in the magnetic housing 243B, 253B, which is arranged to face toward and align with the respective nose support 13, 14 of the frame body 11.

As shown in Fig. 4, each of the magnetic housing 243B, 253B having a L-shaped cross section defines an outer sidewall to bias against an outer side of the shoulder portion 1321, 1421 of the respective nose support 13, 14, wherein the magnet 244B, 254B is received at the outer sidewall of the respective magnetic housing 243B, 253B to define an engaging groove 245B, 255B within an upper wall and the outer sidewall in such a manner that the magnetic seats 242B, 252B are respectively attached to the two nose support 13, 14 by magnetically engaging the two shoulder portions 1321, 1421 of the extension arms 13, 14 in the two engaging grooves 245B, 255B respectively.

Fig. 5 illustrates a third alternative mode of the magnetic seat 242C, 252C wherein each of the magnetic seats 242C, 252C comprises a magnetic housing 243C,

253C extended from the bottom end of the respective supporting arm 241, 251 and a magnet 244C, 254C mounted in the magnetic housing 243C, 253C, which is arranged to face toward and align with the respective nose support 13, 14 of the frame body 11.

As shown in Fig. 5, each of the magnetic housing 243C, 253C having a L-shaped cross section defines an inner sidewall to bias against an inner side of the shoulder portion 1321, 1421 of the respective nose support 13, 14, wherein the magnet 244C, 254C is received at the outer sidewall of the respective magnetic housing 243C, 253C to define an engaging groove 245C, 255C within an upper wall and the inner sidewall in such a manner that the magnetic seats 242C, 252C are respectively attached to the two nose support 13, 14 by magnetically engaging the two shoulder portions 1321, 1421 of the extension arms 13, 14 in the two engaging grooves 245C, 255C respectively.

Fig. 6 illustrates a fourth alternative mode of the magnetic seat 242D, 252D, wherein the shoulder portion 1321D, 1421D is formed at a rear side of the respective extension arm 132D, 142D to magnetically attract with the detachable shelter frame 20D.

Each of the magnetic seats 242D, 252D comprises a magnetic housing 243D, 253D rearwardly extended from the respective supporting arm 241D, 251D and a magnet 244D, 254D mounted in the magnetic housing 243D, 253D, which is arranged to face toward and align with the shoulder portion 1321D, 1421D of the respective nose support 13D, 14D of the frame body 11D when the detachable shelter frame 20D is mounted in front of the primary spectacle frame 10D.

Each magnet 244D, 254D has a thickness smaller than a depth of the respective magnetic housing 243D, 253D so as to define an engaging groove 245D, 255D facing frontwardly when the magnet 244D, 254D is embedded in the magnetic housing 243D, 253D for fittedly engaging with the respective shoulder portion 1321D, 1421D of the respective nose support 13D, 14D, such that the magnetic seats 242D, 252D are respectively attached to the two nose supports 13D, 14D by magnetically engaging the two shoulder portions 1321D, 1421D of the extension arms 13D, 14D in the two engaging grooves 245D, 255D respectively.

As shown in Fig. 6, each of the extension arms 132D, 142D is bent to form the shoulder portion 1321D, 1421D at an inclined manner wherein each of the supporting arms 241D, 251D is rearwardly extended from the shelter frame 21D to inclinedly

support the magnetic seat 242D, 252D with respect to the shoulder portion 1321D, 1421D of the nose support 13D, 14D.

It is worth to mention that each of the magnetic seats 242D, 252D can be modified its structure as shown in Figs. 3, 4, and 5 in order to magnetically engage the magnetic seats 242D, 252D with the shoulder portions 1321D, 1421D of the nose supports 13D, 14D respectively.

Fig. 7 illustrates a fifth alternative mode of the spectacles set according to the preferred embodiment, wherein each extension arm 132E, 142E of the nose supports 13E, 14E is made in U-shape to connect the supporting member 131E, 141E with the frame body 11. The shoulder portion 1321E, 1421E is formed at a lower side of the respective extension arm 132E, 142E to magnetic attract with the detachable shelter frame 20. Accordingly, each of the magnetic seats 242, 252 can be modified to form a structure, as shown in Figs. 1, 3, 4, and 5, to magnetically engage with the shoulder portion 1321E, 1421E of the respective nose support 13E, 14E.

As shown in Fig. 8, a spectacles set according to a second embodiment illustrates an alternative mode of the first embodiment and its alternative modes, wherein the primary spectacle frame 10F and the detachable shelter frame 20F have the similar structural components as shown in the first embodiment, except the nose supports 13F, 14F and the magnetic seats 242F, 252F.

As shown in Figs. 8 and 9, each of the nose supports 13F, 14F comprises a supporting member 131F, 141F and an extension arm 132F, 142F which has a distal end portion extended from the supporting member 131F, 141F and a root end portion extended from the inner side of the respective lens 121F, 122F, wherein each of the extension arm 132F, 142F is made of a kind of metal having magnetic attraction ability, such as mild steel, low carbon steel and high grade steel, which is attractive to magnetic material such as permanent magnet. Each of the extension arms 132F, 142F is bent to form an angled neck portion 1321F, 1421F between the distal end portion and the root end portion.

Each of the magnetic seats 242F, 252F comprises a magnetic housing 243F, 253F rearwardly extended from the respective supporting arm 241F, 251F wherein each magnetic seat 242F, 252F is made of non-magnetic material or soft-magnetic metal

having magnetic attraction ability such as mild steel, low carbon steel and high grade steel and a magnet 244F, 254F mounted in the magnetic housing 243F, 253F, which is arranged to face toward and align with the respective nose support 13F, 14F of the frame body 11F when the detachable shelter frame 20F is mounted in front of the primary spectacle frame 10F.

Each magnet 244F, 254F has a thickness smaller than a depth of the respective magnetic housing 243F, 253F to define an engaging groove 245F, 255F within an surrounding wall of the magnetic housing 243F, 253F and a bottom side of the magnet 244F, 254F when the magnet 244F, 253F is embedded in the magnetic housing 243F, 253F for magnetically engaging with the angled neck portion 1321F, 1421F of the respective nose support 13F, 14F.

As shown in Fig. 9, each of the magnetic housings 243F, 253F further has at least an edge opening 246F, 256F formed at the surrounding wall to communicate with the engaging groove 245F, 255F for fittedly interlocking with the angled neck portion 1321F, 1421F of the respective nose support 13F, 14F. In other words, the detachable shelter frame 20F is securely mounted in front of the primary spectacle frame 10F by not only magnetically mounting the magnetic seats 242F, 252F on the nose supports 13F, 14F within the engaging grooves 245F, 255F respectively but also interlocking the angled neck portions 1321F, 1421F of the nose support 13F, 14F with the edge opening 246F, 256F. In addition, the supporting arms 241F, 251F are arranged to ride on the primary bridge 111 of the frame body 11F to further interlock the detachable shelter frame 20F in front of the primary spectacle frame 10F.

It is worth to mention that the width of the edge opening 246F, 256F is gradually reduced towards the engaging groove 245F, 255F such that when the detachable shelter frame 20F is mounted in front of the primary spectacle frame 10F, the edge opening 246F, 256F substantially guides the angled neck portion 1321F, 1421F of the nose support 13F, 14F to engage with the engaging groove 245F, 255F of the magnetic seat 242F, 252F. In other words, the structure of the edge opening 246F, 256F is adapted to self-adjust the alignment between the nose support 13F, 14F and the magnetic seat 242F, 252F so as to enhance the engagement between the detachable shelter frame 20F and primary spectacle frame 10F.

Fig. 10 illustrates an alternative mode of the spectacles set according to the second embodiment, wherein the supporting arms 241G, 251G are constructed to form the shelter bridge 211F for riding on the primary bridge 111G of the frame body 11G to interlock the detachable shelter frame 20G in front of the primary spectacle frame 10G.

5 Accordingly, each of the extension arms 132F, 142F is bent outwardly to form the angled neck portion 1321F, 1421F to fittedly engage with the edge opening 246F, 256F of the respective magnetic seat 242F, 252F as shown in Fig. 9. Correspondingly, each of the extension arms 132G, 142G can be modified to bend inwardly to form the angled neck portion 1321G, 1421G not only to magnetically attach to the respective  
10 magnetic seat 242G, 252G but also to fittedly engage with the edge opening 246G, 256G of the respective magnetic seat 242G, 252G, as shown in Fig. 10.

As shown in Fig. 11, a spectacles set according to a third embodiment illustrates another alternative mode of the first and second embodiments, which has a similar structure of the above the first and second embodiments and their alternative modes  
15 except the nose supports 13H, 14H.

Each of the nose supports 13H, 14H comprises a supporting member 131H, 141H and an extension arm 132H, 142H which has a distal end portion extended from the supporting member 131H, 141H and a root end portion extended from the inner side of the respective lens 121H, 122H, wherein each of the extension arm 132H, 142H is made  
20 of a kind of metal having magnetic attraction ability, such as mild steel, low carbon steel and high grade steel, which is attractive to magnetic material such as permanent magnet.

Each of the magnetic attachment arrangements 24H, 25H comprises a supporting arm 241H, 251H extending rearwardly from an inner side of the shelter frame 21H towards the respective nose support 13H, 14H for riding on the primary bridge 111H  
25 of the frame body 11H and a magnetic seat 242H, 252H which is connected to the supporting arm 241H, 251H and extended to magnetically attach the respective nose support 13H, 14H of the primary spectacle frame 10H so as to securely hold the shelter frame 21H of the detachable shelter frame 20H in front of the frame body 11H of the primary spectacle frame 10H.

30 Each of the magnetic seats 242H, 252H comprises a magnetic housing 243H, 253H rearwardly extended from the respective supporting arm 241H, 251H wherein each

magnetic seat 242H, 252H is made of non-magnetic material or soft-magnetic metal having magnetic attraction ability such as mild steel, low carbon steel and high grade steel and a magnet 244H, 254H mounted in the magnetic housing 243H, 253H, which is arranged to face toward and align with the respective nose support 13H, 14H of the frame body 11H when the detachable shelter frame 20H is mounted in front of the primary spectacle frame 10H.

Each magnet 244H, 254H has a thickness smaller than a depth of the respective magnetic housing 243H, 253H so as to define an engaging groove 245H, 255H, when the magnet 244H, 254H is embedded in the magnetic housing 243H, 253H for fittedly engaging with the respective distal end portion of the respective nose support 13H, 14H.

It is worth to mention that the distal end portion of each of the extension arms 132H, 142H forms as an engaging member 1321H, 1421H fittedly received in the engaging groove 245H, 255H of the respective magnetic seat 242H, 252H so as to alignedly guide the magnetic seats 242H, 252H to magnetically engage with the extension arms 132H, 142H respectively, as shown in Fig. 12.

Fig. 13 illustrates a first alternative mode of the spectacles set according to the first, second, third embodiments and their alternative modes, wherein the two supporting arms 241J, 251J are rearwardly extended from two lower portions of two inner sides of the shelter frame 21J respectively towards the extension arms 132J, 142J.

Each of magnetic housings 243J, 253J, having a U-shaped cross section, is rearwardly and suspendedly affixed to the rear end of the respective supporting arm 241J, 251J to fittedly engage with the shoulder portion 1321J, 1421J of the respective extension arm 132J, 142J at a position between a distal end portion and a root end portion.

As shown in Fig. 13, the shelter frame 21J further comprises a bridge clip 212J extended between the two auxiliary lenses 221J, 222J for detachably riding on the primary bridge 111J so as to securely mount the detachable shelter frame 20J in front of the primary spectacle frame 10J.

Fig. 14 illustrates a second alternative mode of the spectacles set, wherein the shelter frame 21K of the detachable shelter frame 20K is made of plastic instead of conventional metal frame body. The two supporting arms 241K, 251K are integrally

extended from two inner sides of the auxiliary lenses 221K, 222K towards the nose supports 13K, 14K.

Each of the magnetic seats 242K, 252K comprises a magnetic housing 243K, 253K provided at an outer side of the respective supporting arm 241K, 251K wherein  
5 each magnetic seat 242K, 252K and a magnet 244K, 254K mounted in the magnetic housing 243K, 253K, which is arranged to face toward and align with the respective nose support 13K, 14K of the frame body 11K when the detachable shelter frame 20K is mounted in front of the primary spectacle frame 10K.

As shown in Fig. 14, the magnetic seats 242K, 252K are arranged to  
10 magnetically attach at the root end portions of the extension arms 132K, 142K respectively when the detachable shelter frame 20K is mounted in front of the primary spectacle frame 10K. It is worth to mention that the root end portion of each of the extension arms 132K, 142K is preferably bent to form a loop shape to enlarge its contacting surface to enhance the magnetic connection between the magnetic seat 242K,  
15 252K and the extension arm 132K, 142K.

In addition, the shelter frame 21K further comprises a bridge clip 212K extended between the two auxiliary lenses 221K, 222K for detachably riding on the primary bridge 111K so as to securely mount the detachable shelter frame 20K in front of the primary spectacle frame 10K.

20 One skilled in the art will understand that the embodiment of the present invention as shown in the drawings and described above is exemplary only and not intended to be limiting.

It will thus be seen that the objects of the present invention have been fully and effectively accomplished. Its embodiments have been shown and described for the  
25 purposes of illustrating the functional and structural principles of the present invention and is subject to change without departure from such principles. Therefore, this invention includes all modifications encompassed within the spirit and scope of the following claims.